



# SMALL SYSTEM DATA SHEET



## HLI LIGHT COMMERCIAL

Inputs - 3 - Line, Mic/line with 5 volts of phantom power, and digital inLOOP Connector (optional).  
Package contains amplifier, power supply, 200' of 18 gauge wire and analog audio cable  
Maximum room and enclosure temperatures must be below 140 degree fahrenheit.  
Power requirements - 100 - 240 volts AC ~ 50/60Hz 60 volt/amps  
Coverage - IEC 60118-4 compliant as tested at 1200 sq ft  
Controls - Tone control. Loop volume control.  
Dimensions - 6" x 4" x 2" 3 lbs  
Power Supply Approvals - UL ULC CE



## HLI DIGITAL CONNECTOR

Self powered 5.1 Channel Digital input for inLOOP hearing loop equipment.  
Supports MP3/AC3/DTS/WAV/WMA/AAC/APE/ALAC/FLAC/OGG & M4A formats.  
Inputs - Digital coax and optical (including Dolby Digital ©).  
Package contains Digital inLOOP Connector and an optical cable.  
Dimensions - 6" x 4" x 1" 1 lbs



## HLI HOME LOOP

Inputs - Switchable analog Mic/line with 5 volts of phantom power, and digital inLOOP Connector (optional).  
Package contains amplifier, power supply, 150' of 20 gauge wire and analog audio cable.  
Power requirements - 100 - 240 volts AC ~ 50/60Hz 18 volt/amps  
Coverage - IEC 60118-4 compliant as tested at 600 sq ft.  
Controls - Tone control. Loop volume control. Power switch.  
Dimensions - 7" x 2.75" x 3.125" 3 lbs  
Power Supply Approvals - UL ULC CE



## PERSONAL PAD ANTENNA

Package contains Personal loop pad with 33' of 22 gauge wire.  
Dimensions - 16" x 16" x .125" 1 lbs



## HLI COUNTER LOOP

Package contains amplifier, power supply, loop antenna, velcro and microphone.  
Power requirements - 100 - 240 volts AC ~ 50/60Hz 18 volt/amps  
Controls - Tone control. Loop volume control. Power switch.  
Dimensions - 7" x 2.75" x 3.125" 4 lbs  
Power Supply Approvals - UL ULC CE



**SMALL SYSTEM WARRANTY** - This limited lifetime warranty covers the loop amplifier and enclosure. The loop amplifier is warranted to be free of defects in material and workmanship for the life of the product under the following schedule and conditions: The warranty does not cover damage from misuse, power surges or improper installation. We will provide ground shipping, and repair systems that meet these criteria for six months. We will repair and provide return shipping from six months to twenty-four months. For the remainder of the life of the product we will repair systems that meet these criteria with the customer providing shipping. Cords, cables and power supplies are warranted to be free of defects in material and workmanship for a period of one year.

**HEARING LOOP INC products are made in the USA** Some cables, power supplies and electronic components attached to the circuit boards are not available in our country and have to be imported.